

CFRP ADHESIVE JOINTS AND STRUCTURES FOR OFFSHORE WIND-LENS TURBINE

Abusrea, M R

Interdisciplinary Graduate School of Engineering Science, Kyushu University

Jiang, Shiyi

Interdisciplinary Graduate School of Engineering Science, Kyushu University

Chen, Dingding

National University of Defense Technology

Arakawa, Kazuo

Research Institute for Applied Mechanics, Kyushu University

<https://doi.org/10.15017/1809211>

出版情報 : Proceedings of International Exchange and Innovation Conference on Engineering & Sciences (IEICES). 1, pp.1-, 2015-10-15. 九州大学大学院総合理工学府

バージョン :

権利関係 :



CFRP ADHESIVE JOINTS AND STRUCTURES FOR OFFSHORE WIND-LENS TURBINE

M R Abusrea¹, Shiyi Jiang¹, Dingding Chen², and Kazuo Arakawa³.

¹ Interdisciplinary Graduate School of Engineering Science, Kyushu University, Fukuoka, Japan
(mahmoud.r.abusrea.127@s.kyushu-us.ac.jp)

² National University of Defense Technology, China,

³ Research Institute for Applied Mechanics, Kyushu University, Fukuoka, Japan

Abstract: *Novel wind-lens turbine designs can augment power output. Vacuum-assisted resin transfer molding (VARTM) is used to form large and complex structures from a carbon fiber reinforced polymer (CFRP) composite. Typically, wind-lens turbine structures are fabricated in segments, and then bonded to form the final structure. This paper introduces five new adhesive joints, divided into two groups: one is constructed between dry carbon and CFRP fabrics, and the other is constructed with two dry carbon fibers. All joints and CFRP fabrics were made in our laboratory using VARTM manufacturing techniques. Specimens were prepared for tensile testing to measure joint performance. The results showed that the second group of joints achieved a higher tensile strength than the first group. On the other hand, the tensile fracture behavior of the two groups showed the same pattern of crack originating near the joint ends followed by crack propagation.*